
## Icon Valves & Engineering Pvt. Ltd. www.flushbottomvalve.net; fbv@ivevalves.com



FLUSH TANK BOTTOM VALVE FLANGE ENDS DISC LOWERING INTO THE VALVE-SHORT HUB 150#



FLUSH TANK BOTTOM VALVE FLANGE END DISC LOWERING INTO THE VALVE WITH SENSOR										
SIZE	(mm)	Approx.			Approx.	(FLANGE DIMENSIONS)		(FLANGE DIMENSIONS)		APPROX. WT. / KG
IN	OUT	L	Н	D	W	l l	T	0	T1	
3/4"	3/4"	325	ı.	† †	105	AS PER 3/4" NB ASA 150#	11.0	AS PER 3/4" NB ASA 150#	11.0	06
1"	3/4"	325	1 1		105	AS PER 1" NB ASA 150#	11.0	AS PER 3/4" NB ASA 150#	11.0	07
1"	1"	350			125	AS PER 1" NB ASA 150#	11.0	AS PER 1" NB ASA 150#	11.0	08
1.1/2"	1"	350			125	AS PER 1.1/2" NB ASA 150#	14.0	AS PER 1" NB ASA 150#	11.0	09
1.1/2"	1.1/2"	380			156	AS PER 1.1/2" NB ASA 150#	14.0	AS PER 1.1/2" NB ASA 150#	14.0	10
2"	1.1/2"	400	CLIENT	CLIENT	156	AS PER 2" NB ASA 150#	16.0	AS PER 1.1/2" NB ASA 150#	14.0	11
2"	2"	425	34 CL	34 CL	176	AS PER 2" NB ASA 150#	16.0	AS PER 2" NB ASA 150#	16.0	12
3"	2"	450			176	AS PER 3" NB ASA 150#	19.0	AS PER 2" NB ASA 150#	16.0	14
3"	3"	500	CIFIED	CIFIED	219	AS PER 3" NB ASA 150#	19.0	AS PER 3" NB ASA 150#	19.0	21
4"	3"	500	SPE	SPE	219	AS PER 4" NB ASA 150#	24.0	AS PER 3" NB ASA 150#	19.0	24
4"	4"	550	BE 9	BE	252	AS PER 4" NB ASA 150#	24.0	AS PER 4" NB ASA 150#	24.0	33
6"	4"	600	욘	욘	252	AS PER 6" NB ASA 150#	25.0	AS PER 4" NB ASA 150#	24.0	39
6"	6"	800			305	AS PER 6" NB ASA 150#	25.0	AS PER 6" NB ASA 150#	25.0	65
8"	6"	800			305	AS PER 8" NB ASA 150#	28.0	AS PER 6" NB ASA 150#	25.0	75
8"	8"	950	'	'	400	AS PER 8" NB ASA 150#	28.0	AS PER 8" NB ASA 150#	28.0	90

SR NO.	DESCRIPTION	MATERIAL	QTY.
01	BODY	ASTM A216 WCB, ASTM A351 / CF8 / CF8M / CF3 / CF3M / CN7M	1
02	DISC	ASTM A216 WCB, ASTM A351 / CF8 / CF8M / CF3 / CF3M / CN7M	1
03	SEAT	ASTM A216 WCB, ASTM A351 / CF8 / CF8M / CF3 / CF3M / CN7M	1
04	STEM	AISI 304/316/304L/316L/A20	1
05	GLAND	AISI 304	1
06	YOKE BUSH HOUSING	AISI 304	1
07	COUPLER	M.S.	1
08	GLAND PACKING	PTFE/GF/CF PTFE	- 1
09	HAND WHEEL	SS 304 / CI	1

TECHNICAL DATA						
DESIGN & MANUFACTURING STD.	MANUFACTURERS STD. / ANSI B-16.34					
TESTING & INSPECTION STD.	API 598					
END CONNECTIONS:	FLANGED AS PER ANSI B-16.5 CLASS-150#.					



PRIMARY SERVICE RATING & TEST PRESSURE						
CLASS	WORKING	HYD. TEST_PRESSURE				
	PRESS.	BODY	SEAT	TEMP.		
150	150 PSIG	425 PSIG	300 PSIG	38° C		
AIR TEST -	SEAT	80 PSIG ±10 PSIG				

NOTE: This Drawing, Catalogue, Photograps & Information there of are sole & Exclusive Property of "TVE", know Yelve & Exclusive Property of "TVE", know Yelve & Explanearing Pvt. Ltd. Mumbail. it cannot be Copied, Distributed or Circulated to any other firm, Parry or Individual without prin Notes. The dimensions, Drawing & Photographs libratrated are approximate & may some time from the actual product. Please ask for final Drawings & Photos against orders.