



ICON VALVES & ENGINEERING PVT LTD

www.flushbottomvalves.net

www.ivevalves.net

E mail:

valves@ivevalves.com

fbv@ivevalves.com

FACE TO FACE / END TO END DIMENSIONS OF VALVES (in mm)

SIZE (MM-NB)	15	20	25	40	50	65	80	100	125	150	200	250	300
FACE TO FACE DIMENSION - (ANSI B 16.10)													
GATE VALVES (Flanged Ends)													
LASS - 150	10	118	127	165	178	190	203	229	254	267	292	330	356
LASS - 300	14	152	165	190	216	241	283	305	381	403	419	457	502
LASS - 600	16	190	216	241	292	330	356	432	508	559	NA	NA	NA
GLOBE VALVES (Flanged Ends)													
LASS - 150	10	118	127	165	203	216	241	292	356	406	495	622	698
LASS - 300	15	178	203	229	267	292	318	356	400	445	559	622	711
LASS - 600	165	190	216	241	292	330	356	432	508	559	NA	NA	NA
SWING CHECK (Flanged Ends)													
LASS - 150	N	NA	NA	165	203	216	241	292	356	356	495	622	699
LASS - 300	N	NA	NA	241	267	292	318	356	400	445	533	622	711
LASS - 600	N	NA	NA	241	292	330	356	432	508	559	NA	NA	NA
BALL VALVES One PC / Two PC / Three PC (Flanged Ends)													
LASS - 150	10	118	127	165	178	190	203	229	NA	267	292	330	356
LASS - 300	14	152	165	190	216	241	283	305	NA	403	419	457	502
GLOBE VALVES (Flanged Ends) - DIN STANDARD													
LASS - 150	13	150	160	160	200	290	310	350	400	480	600	730	850
LASS - 300	13	150	160	160	200	290	310	350	400	480	600	730	850

END TO END DIMENSIONS - (Socket Weld / Screwed Ends)

BALL VALVES					
THREE PIECE	95	95	100	120	140
ONE PIECE	70	85	95	115	135
FORGED GATE / GLOBE / CHECK VALVES					
CLASS - 800	85	92	104	127	140
SOCKET BORE	27.1	27.1	33.8	48.6	61.1
SOCKET BORE DEPTH	9.5	12.7	12.7	12.7	16

TEST PROCEDURE : Conforming to API 598 / BS 5146 / DIN STD

TEST PRESSURES :				
RATINGS	HYDROSTATIC TEST		AIR TEST	
	BODY		SEAT	
	PSIG	Kg / cm ² G	PSIG	Kg / cm ² G
CLASS - 150	450	32	315	22
CLASS - 300	1125	79	815	57
CLASS - 600	2225	156	1630	115
CLASS - 800	3000	211	2000	141
DIN ND - 16	----	32	----	16
DIN ND - 40	----	64	----	40